

The Matthiesen Drying Belt System

Matthiesen's drying belt systems can help you put more quality ice in the bag to increase your profits. Drying belts may be ordered in a minimum length of 10 feet and increased in one foot increments; in a minimum width of 2 feet and increased in one foot increments.

Specifications

Length	Minimum 10' Length can be extended in 1' increments to any length
Width	2' - 6', etc.
Construction	Standard galvanized body Stainless steel available
Electrical	230-460/3/60 Other electrical available
Motor	Sized according to ice load per minute and length of belt Motors are TEFC*. Wash down available
FPM	Standard is 36 feet per minute Other FPM available
Belting	Standard is stainless steel 1/2" x 1" chain mesh Other sized mesh available Other types of belting available Easy belt tensioner
Wear Strips	Standard UHMW runners for less ice build-up, with heater strips Drying belt is broken down easily for confined installation

* Totally Enclosed Fan Cooled



Manufacturers & Suppliers To Ice Industry Since 1945

Product should be installed in compliance with NEC (National Electric Code), OSHA, and other regulatory agencies. All specifications are subject to change without notice.

Standard Features

- Standard stainless steel shafts
- Standard polyethylene sprockets for less ice build-up with suspended hangers
- Heater on top runner for less ice build-up
- Standard wear strips - UHMW runners for less ice build up, with heater strips. Drying belt is broken down easily for confined installation.

Options

- Ice spreader hopper

For sales assistance call your authorized Matthiesen distributor